

Bảng thông số sản phẩm

Đặc điểm

MIP22212

Enclosure, Resi9 MP, flush mounting, 2 rows of 12 modules, IP40, white door, 1 earth + 1 neutral terminal blocks



Main

Range	Resi9
Product name	Resi9 MP
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12
Nb of horizontal rows	2
Type of door	Plain
Width	270 mm wall: 294 mm outside:
Height	353 mm wall: 377 mm outside:
Depth	18 mm outside: 80 mm wall: 98 mm total:
Built-in depth	80 mm

Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 16 outgoers

1 neutral (screwed) with 16 outgoers

Distribution block outgoers	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 6 x 6 mm ² for earth 6 x 6 mm ² for neutral 8 x 10 mm ² for earth 8 x 10 mm ² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	76 mm
Colour	Door: white (RAL 9003) Front face: white (RAL 9003)
Market segment	Small commercial Residential

Environment

Standards	IEC 60695-2-11 IEC 60439-3 IEC 60670-24 IEC 529 EN 50102
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.401 kg
Package 1 Height	9.1 cm
Package 1 width	29.5 cm
Package 1 Length	37.7 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	7.51 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	52 cm
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Weight	138.104 kg
Package 3 Height	1350 cm
Package 3 width	800 cm
Package 3 Length	1200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------